

Technical Data Sheet

Giorgio Graesan PRIMUS AGGRAPPANTE

Effective from 30 May 2019

Description

Giorgio Graesan Primus Aggrappante is a levelling base primer for use before applying other Giorgio Graesan products. It is easy to apply

Uses

Suitable for the preparation of indoor wall surfaces prior to the application of other Giorgio Graesan decorative wall coverings. Suitable as a smoothing base material for priming tiled surfaces prior to the application of other Giorgio Graesan decorative finishes

Can be applied over any standard building substrate following correct surface preparation

| Colour | White to off-white colour |
|--|---------------------------|
| Sheen Level | Flat finish |
| Coverage Rate | 600 ml per m2 |
| Application Method | Roller |
| Typical Data at 25'C and 50% Relative Humidity | |

| Drying Time | 24 hours |
|---------------------|---------------------------|
| Curing Time | 24 hours |
| Usual No of Coats | One coat |
| Clean Up | Water |
| Packaging Sizes | 2.5L, 5L |
| Abrasion Resistance | Not applicable |
| Water Resistance | Not applicable |
| VOC | 17g/L – Classified as Low |



Technical Data Sheet

Giorgio Graesan PRIMUS AGGRAPPANTE

Effective from 30 May 2019

Pot Life Once opened, use within 12 months. Store in a cool, dry and well ventilated place, away from sources of heat and from direct sunlight

Substrate Conditions

Substrate must be installed as per manufacturer's specifications prior to application

Substrate must be clean and free of dust, dirt, oil, salt, mould or any other contamination

Any base coats should be fully cured

For full details on application for each substrate refer to the Giorgio Graesan Specification and System Guide

Mixing

Primus Aggrappante is pre mixed and comes ready to use. Product will need to be mixed thoroughly before use.

Application

Apply Primus Aggrappante with a" toothed" Trowel, ensuring full, even coverage of the surface *area*.

Precautions and Limitations

Adequate PPE should be used when mixing and applying product

Do not apply if the temperature will fall below 5'C or above 35'C during application.

Do not apply in direct sunlight, wind or rain and protect the finished work until fully cured

Transport and Storage

Store in a cool, dry place

Keep pail sealed when not in use



Technical Data Sheet

Giorgio Graesan PRIMUS AGGRAPPANTE

Effective from 30 May 2019

Disposal

Dispose of in accordance with local council regulations

Safety Data

Refer to Giorgio Graesan Primus Aggrappante Plaster SDS

Giorgio Graesan will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement, Giorgio Graesan Australia reserves the right to change these specifications without further notice. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.